

*CLAIM AMENDMENTS*

1. (Currently amended) A retainer clip for mounting a flanged sink to a countertop in which the flange seats against the countertop, the retainer clip comprising:  
a ratchet plate mounted to an edge of the countertop, the ratchet plate including a front face sinkwardly directed and having a plurality of detents, each of the detents including a generally horizontal groove on the front face of the ratchet plate, the detents being aligned parallel to each other; and

a pawl mounted to the sink and configured to deflectably engage at least one of the detents of the ratchet plate when the sink is inserted downwardly into the countertop and to upwardly seat in said one of the detents to retain the sink in a fully inserted position.

2. (Canceled)

3. (Currently amended) The retainer clip of claim 2 1, wherein each of the detents is a generally V-shaped groove formed by two surfaces disposed at a generally right angle relative to each other.

4. (Currently amended) The retainer clip of claim 2 1, wherein the ratchet plate includes a stop which extends rearwardly from an upper edge of the ratchet plate to seat against an upper surface of the countertop.

5. (Original) The retainer clip of to claim 1, wherein the pawl includes at least one resilient tab which deflectably engages the ratchet plate.

6. (Currently amended) A retainer clip for mounting a flanged sink to a countertop in which the flange seats against the countertop, the retainer clip comprising:  
a ratchet plate mounted to an edge of the countertop, the ratchet plate including a front face sinkwardly directed and having a plurality of detents; and  
a pawl including ~~The retainer clip of claim 5, wherein the pawl includes a plurality of resilient tabs, at least some of the tabs having respectively different lengths, mounted to the~~

sink and configured to deflectably engage at least one of the detents of the ratchet plate when the sink is inserted downwardly into the countertop and to upwardly seat in said one of the detents to retain the sink in a fully inserted position.

7. (Original) The retainer clip of claim 6, wherein a difference in vertical dimension among at least some of the tabs is less than an incremental vertical distance between adjacent detents in the ratchet plate.

8. (Original) The retainer clip of claim 6, wherein the pawl is a unitary spring element which includes at least one slot defining a separation between adjacent tabs.

9. (Original) The retainer clip of claim 6, wherein the pawl includes: a base portion which is securable relative to the sink; a body portion projecting from the base portion at an upwardly oblique angle in a direction generally outwardly from the sink; and a tip portion opposite the base end, the tip being shaped to complementarily seat in the detents.

10. (Original) The retainer clip of claim 9, further comprising a mount assembly adapted to fixedly secure the base portion of the resilient tab relative to a rail of the sink under the sink flange, wherein the mount assembly is adapted to be mounted to a rail extending along an underside of the sink flange, the mount assembly including at least one screw hole, the mount assembly including a screw adapted to extend through the screw hole to secure the base end of the resilient tab relative to the rail.

11. (Previously Amended) The retainer clip of claim 9, wherein the pawl includes a mount assembly adapted to fixedly secure the base portion of the pawl relative to a generally U-shaped channel rail of the sink under the sink flange, the mount assembly including at least one screw having a head shaped to be slidably received within an interior cavity of the channel rail, the screw having a threaded portion projecting outwardly from the interior cavity, the base end of the tab including a hole for receiving the threaded portion of the screw, the mount assembly further including a nut to secure the resilient tab relative to the rail.

12. (Previously Amended) The retainer clip of claim 11, wherein the screw head is shaped to prevent rotation of the screw relative to the channel rail.

13. (Previously Amended) A retainer clip for anchoring a flanged sink within a cutout of a countertop, the retainer clip comprising:

a ratchet plate mounted to an edge the countertop within the cutout, the ratchet plate including a front face sinkwardly directed and having a plurality of parallel detents respectively spaced from each other by an incremental distance; and

a pawl mounted to the sink, the pawl including a plurality of resilient tabs, each of the tabs configured to deflectably engage the ratchet plate and to engage successive detents with a one-way locking action as the pawl moves vertically relative to the ratchet plate;

wherein at least some of the resilient tabs have different respective lengths so that when at least one of the tabs is seated upwardly in a detent, at least one of the other tabs is positioned between detent increments.

14. (Original) The retainer clip of claim 13, wherein each of the detents is a generally V-shaped groove formed by two surfaces disposed at a generally right angle relative to each other.

15. (Original) The retainer clip of claim 13, wherein the ratchet plates includes a stop which extends rearwardly from an upper edge of the ratchet plate to seat against an upper surface of the countertop.

16. (Original) The retainer clip of claim 13, wherein the pawl is unitary and includes: a base portion which is securable relative to the sink; a body portion projecting from the base portion at an upwardly oblique angle in a direction generally outwardly from the sink; and a tip portion opposite the base end, the tip being shaped to complementarily seat in the detents.

17. (Currently amended) A combination comprising:  
a sink including a peripheral flange for seating against a countertop and a plurality of rails mounted to an underside of the peripheral flange; and  
a plurality of retainer clips for mounting the sink within a cutout of a countertop, each of the retainer clips including:  
a ratchet plate mountable to an edge of the cutout, the ratchet plate including a front face having a plurality of detents positioned vertically adjacent to each other, each of the detents including a generally horizontal groove on a front face of the ratchet plate, the detents being aligned parallel to each other; and  
a pawl mounted to the rail of the sink and including at least one resilient tab to deflectably engage successive detents of the ratchet plate when the sink is inserted downwardly into the cutout and to upwardly seat in one of the detents to retain the sink in a fully inserted position when the flange seats against the countertop.

18. (Canceled)

19. (Currently amended) The combination of claim 17 ~~18~~, wherein each of the detents is a generally V-shaped grooved.

20. (Original) The combination of claim 17, wherein the ratchet plate includes a stop which extends rearwardly from an upper edge of the ratchet plate to seat against an upper surface of the countertop.

21. (Currently amended) A combination comprising:  
a sink including a peripheral flange for seating against a countertop and a plurality of rails mounted to an underside of the peripheral flange; and  
a plurality of retainer clips for mounting the sink within a cutout of a countertop, each of the retainer clips including:  
a ratchet plate mountable to an edge of the cut out, the ratchet plate including a front face having a plurality of detents positioned vertically adjacent to each other; and

a pawl mounted to the rail of the sink and including ~~The combination of claim 17,~~  
~~wherein the panel includes~~ a plurality of resilient tabs, at least some of the tabs having  
respectively different lengths, to deflectably engage successive detents of the ratchet plate  
when the sink is inserted downwardly in to the cutout and to upwardly seat in one of the  
detents to retain the sink in a fully inserted position when the flange seats against the  
countertop.

22. (Original) The combination of claim 21, wherein a difference in vertical dimension among at least some of the tabs is less than an incremental vertical distance between adjacent detents in the ratchet plate.

23. (Original) The combination of claim 21, wherein the pawl is a unitary member and the plurality of tabs are formed by at least one slot defining a separation between adjacent tabs.

24. (Original) The combination of claim 23, wherein the pawl includes: a base portion which is fixed relative to the sink, a body portion projecting from the base portion at an upwardly oblique angle in a direction generally outwardly from the sink; and a tip portion opposite the base end, the tip being shaped to complementarily seat in the detents.

25. (Original) The combination of claim 24, wherein the sink includes a rail extending under the flange and further comprising at least one screw securing the base portion of the pawl to the rail.

26. (Previously Amended) The combination of claim 24, wherein the sink includes a generally U-shaped channel rail extending along an underside of the flange, further comprising at least one screw head disposed within an interior cavity of the channel rail, the screw having a threaded portion projecting outwardly from the interior cavity, a hole extending through the base portion of the pawl and a nut securing the resilient tab relative to the rail.

In re Appln. of White et al.  
Application No. 10/045,572

27. (Original) The combination of claim 26, wherein the screw head is shaped to prevent rotation of the screw relative to the channel rail.

28. (Original) The combination of claim 26, wherein the channel further includes a pair of opposed ridges which project inwardly along an opening to the interior cavity, the screw head seating against the ridges.